

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
13 October 2005 (13.10.2005)

PCT

(10) International Publication Number
WO 2005/096242 A3

(51) International Patent Classification⁷: **G08C 17/00**,
H05B 37/02, H01L 23/467

(21) International Application Number:
PCT/GB2005/001196

(22) International Filing Date: 29 March 2005 (29.03.2005)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
0406983.7 29 March 2004 (29.03.2004) GB

(71) Applicant and

(72) Inventor: **BRISON, Paul, Stanley** [US/GB]; 15 Andrew
Baxter Avenue, Shawsburn Village, Ashgill, Larkhall La-
narkshire ML9 3RG (GB).

(74) Agents: **HACKNEY, Nigel** et al.; Mewburn Ellis LLP,
York House, 23 Kingsway, London Greater London WC2B
6HP (GB).

(81) Designated States (unless otherwise indicated, for every
kind of national protection available): AE, AG, AL, AM,
AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN,

CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI,
GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE,
KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD,
MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG,
PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SM, SY,
TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU,
ZA, ZM, ZW.


(84) Designated States (unless otherwise indicated, for every
kind of regional protection available): ARIPO (BW, GH,
GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM,
ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),
European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI,
FR, GB, GR, HU, IE, IS, IT, LT, LU, MC, NL, PL, PT, RO,
SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN,
GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

- with international search report
- before the expiration of the time limit for amending the
claims and to be republished in the event of receipt of
amendments

[Continued on next page]

(54) Title: APPARATUS AND METHOD OF POWER CONTROL



(57) Abstract: A power controller for controlling power delivery to a light, the power controller having a control unit in a weather proof casing responsive not only to remote power control signals, but also to be responsive to a remote stimulus with which the mode of operation of the power controller may be controlled. The power controller may include the casing, the control unit disposed within the casing, and a heat sink means disposed within the casing in a space between the control unit and parts of the casing, the heat sink means including a group of vane members each positioned in an array of vane members collectively surrounding at least a part of the control unit in which vane members are arranged to partially overlap other vane members (e.g. neighbouring vane of the array) in separated opposition thereto to define fluid ventilation ducts (e.g. for fluid inlet and/or outlet).



(88) Date of publication of the international search report:

19 January 2006

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.